

Product Description

General	Aluminum cassette profile held firmly by PVC coated steel cables and 0.24" (6mm) wide EPDM spacer for fall-thru action
Aesthetic aspect	Ribbed carpet wipers, Black EPDM spacers with open construction

Technical Specifications

Physical Properties

Thickness	19/20" (24mm)
Wiper surface	1.02" (26mm)
Cassette profile material	Mill Finished Aluminum, grade 6063-T6
Wiper strip material	Heavy Duty Ribbed Carpet
Connector material	PVC coated Stainless Steel cables
Spacer material	Black E.P.D.M.
Wiper Spacing	15/64" (6mm)
Format	Roll-able
Design	Open
Mat module size	3' FB x 9.84' LR (914mm FB x 3000mm LR)
Weight / Square Meter	35.27 lbs (16 kgs)
Maximum rolling load / wheel, Recessed installation	1000 lbs.
Frame options	Welcome mat-well frame of silver anodized aluminum, grade 6063-T6

Component Color Options

Carpet Wiper strip	Brown, Blue, Grey, Black (custom colors available MOQ applied)
--------------------	--

Product Properties

Performance	Standard	Result
Critical Radiant Flux	ASTM E648	Class 1
Coefficient of Friction	ASTM D2047	Meets or exceeds ADA guidelines
Rolling Load	ASTM F2753	Able to sustain 1000 passes without damage
Corrosion (Salt Spray)	ASTM B117	Able to sustain 100 hours of salt fog without any notable changes

LEED

MR Credit 4	LEED-NC v.3	For 1-2 points: value of all materials = min. average 10% recycled content	40% pre-consumer and 40% post-consumer recycled
IEQ Credit 5	LEED-NC v.3	For 1 point: permanently installed entrance mats at least 10' long	Mat designed for permanent installation